

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

10-21-1969

Test 1026: Ford 8000 Diesel Dual Power (Also Ford 8000 Diesel Dual Power Row Crop)

Tractor Museum

University of Nebraska-Lincoln, TractorMuseumArchives@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

Museum, Tractor, "Test 1026: Ford 8000 Diesel Dual Power (Also Ford 8000 Diesel Dual Power Row Crop)" (1969). *Nebraska Tractor Tests*. 1363.

<https://digitalcommons.unl.edu/tractormuseumlit/1363>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 1026 – FORD 8000 DIESEL DUAL POWER (ALSO FORD 8000 DIESEL DUAL POWER ROW CROP)

POWER TAKE-OFF PERFORMANCE

| Hp | Crank- shaft speed rpm | Fuel Consumption | | Temperature Degrees F | | | | | |
|---|---------------------------------|------------------|--------------------|-----------------------|-------------------|--------------------|--------------------|-----------------------------------|--------|
| | | Gal per hr | Lb per hp-hr | Hp-hr per gal | Cooling medium | Air wet bulb | Air dry bulb | Barometer inches of Mercury | |
| MAXIMUM POWER AND FUEL CONSUMPTION | | | | | | | | | |
| Rated Engine Speed—Two Hours | | | | | | | | | |
| 105.73 | 2300 | 6.756 | 0.444 | 15.65 | 183 | 58 | 75 | 29.248 | |
| Standard Power Take-off Speed (1000 rpm)—One Hour | | | | | | | | | |
| 94.33 | 1935 | 5.638 | 0.416 | 16.73 | 180 | 53 | 75 | 29.270 | |
| VARYING POWER AND FUEL CONSUMPTION—TWO HOURS | | | | | | | | | |
| 94.26 | 2408 | 6.207 | 0.458 | 15.19 | 175 | 54 | 76 | | |
| 0.00 | 2514 | 2.204 | | | 136 | 52 | 73 | | |
| 48.36 | 2471 | 4.046 | 0.582 | 11.95 | 154 | 53 | 75 | | |
| 106.35 | 2300 | 6.763 | 0.442 | 15.73 | 183 | 55 | 77 | | |
| 24.27 | 2497 | 2.998 | 0.859 | 8.10 | 147 | 53 | 75 | | |
| 71.34 | 2436 | 5.021 | 0.489 | 14.21 | 165 | 53 | 74 | | |
| Av | 57.43 | 2438 | 4.540 | 0.550 | 12.65 | 160 | 53 | 75 | 29.247 |

DRAWBAR PERFORMANCE

| Hp | Draw- bar pull lbs | Speed miles per hr | Crank- shaft speed rpm | Slip of drivers % | Fuel Consumption | | Temp Degrees F | | | | Barom- eter inches of Mercury |
|----|-----------------------------|-----------------------------|---------------------------------|----------------------------|------------------|--------------------|---------------------|---------------------|--------------------|--------------------|--|
| | | | | | Gal per hr | Lb per hp-hr | Hp-hr per gal | Cool- ing med | Air wet bulb | Air dry bulb | |

VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST

| | | | | | | | | | | | |
|--|------|------|------|------|-------|-------|-------|-----|----|----|--------|
| Maximum Available Power—Two Hours—8th (5PD) Gear | | | | | | | | | | | |
| 92.61 | 7058 | 4.92 | 2301 | 6.68 | 6.758 | 0.508 | 13.70 | 163 | 46 | 53 | 29.215 |
| 75% of Pull at Maximum Power—Ten Hours—8th (5PD) Gear | | | | | | | | | | | |
| 75.99 | 5400 | 5.28 | 2420 | 4.68 | 5.974 | 0.547 | 12.72 | 162 | 55 | 64 | 29.061 |
| 50% of Pull at Maximum Power—Two Hours—8th (5PD) Gear | | | | | | | | | | | |
| 52.54 | 3633 | 5.42 | 2450 | 3.37 | 4.796 | 0.635 | 10.95 | 148 | 48 | 52 | 29.050 |

MAXIMUM POWER WITH BALLAST

| | | | | | | | | | | | |
|-------|-------|-------|------|-------|-----------------|--|--|-----|----|----|--------|
| 79.91 | 11362 | 2.64 | 2390 | 12.50 | 4th Gear (2DD) | | | 149 | 40 | 46 | 29.150 |
| 88.52 | 11073 | 3.00 | 2299 | 11.63 | 5th Gear (3PD) | | | 150 | 39 | 45 | 29.170 |
| 89.18 | 8309 | 4.03 | 2300 | 7.83 | 6th Gear (3DD) | | | 163 | 46 | 53 | 29.260 |
| 93.43 | 8367 | 4.19 | 2301 | 7.83 | 7th Gear (4PD) | | | 165 | 46 | 53 | 29.260 |
| 93.95 | 7190 | 4.90 | 2295 | 6.64 | 8th Gear (5PD) | | | 168 | 47 | 56 | 29.250 |
| 88.88 | 6045 | 5.51 | 2300 | 5.50 | 9th Gear (4DD) | | | 167 | 47 | 56 | 29.250 |
| 90.52 | 5269 | 6.44 | 2299 | 4.73 | 10th Gear (5DD) | | | 167 | 47 | 55 | 29.250 |
| 94.58 | 5000 | 7.09 | 2302 | 4.73 | 11th Gear (6PD) | | | 166 | 47 | 54 | 29.220 |
| 87.87 | 3561 | 9.25 | 2303 | 3.13 | 12th Gear (6DD) | | | 165 | 48 | 56 | 29.220 |
| 89.41 | 3101 | 10.81 | 2297 | 3.05 | 13th Gear (7PD) | | | 164 | 47 | 56 | 29.220 |
| 79.88 | 2130 | 14.06 | 2300 | 2.15 | 14th Gear (7DD) | | | 161 | 47 | 55 | 29.220 |
| 83.45 | 2126 | 14.72 | 2313 | 1.98 | 15th Gear (8DD) | | | 159 | 46 | 54 | 29.220 |

MAXIMUM PULL WITHOUT BALLAST

| | | | | | | | | | | | |
|-------|------|------|------|-------|----------------|--|--|-----|----|----|--------|
| 73.39 | 9003 | 3.06 | 2423 | 14.95 | 5th Gear (3PD) | | | 142 | 46 | 49 | 28.910 |
|-------|------|------|------|-------|----------------|--|--|-----|----|----|--------|

VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST 8th (5PD) Gear

| | | | | | | |
|----------------------|-------|-------|-------|-------|-------|-------|
| Pounds Pull | 7190 | 7486 | 7804 | 7944 | 8018 | 7726 |
| Horsepower | 93.95 | 87.86 | 81.09 | 72.03 | 62.37 | 49.98 |
| Crankshaft speed rpm | 2295 | 2068 | 1836 | 1609 | 1380 | 1145 |
| Miles per hour | 4.90 | 4.40 | 3.90 | 3.40 | 2.92 | 2.43 |
| Slip of drivers, % | 6.64 | 6.87 | 7.32 | 7.61 | 7.61 | 7.46 |

TIRES, BALLAST and WEIGHT

| | | With Ballast | Without Ballast |
|----------------------------------|----------------------|---------------------|---------------------|
| Rear tires | —No, size, ply & psi | Two 23.1-34; 8; 16 | Two 23.1-34; 8; 16 |
| Ballast | —Liquid | 1878 lb each | None |
| | Cast iron | None | None |
| Front tires | —No, size, ply & psi | Two 10.00-16; 6; 28 | Two 10.00-16; 6; 28 |
| Ballast | —Liquid | None | None |
| | Cast iron | None | None |
| Height of drawbar | | 22 inches | 23 inches |
| Static weight with operator—Rear | | 11380 lb | 7625 lb |
| Front | | 3420 lb | 3445 lb |
| Total | | 14800 lb | 11070 lb |

Department of Agricultural Engineering

Dates of Test: October 21 to October 30, 1969

Manufacturer: FORD MOTOR COMPANY,
FORD TRACTOR OPERATIONS, BIR-
MINGHAM, MICHIGAN

FUEL, OIL and TIME Fuel No 2 diesel Cetane No 52.2 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.8353 Weight per gallon 6.955 lb Oil SAE 10W API service classification MS-DS To motor 2.682 gal Drained from motor 1.983 gal Transmission and final-drive lubricant Ford oil M-2C53-B or ESN-N2C53-A Total time engine was operated 44 hours.

ENGINE Make Ford Diesel Type 6 cylinder vertical Serial No G127084 Crankshaft mounted lengthwise Rated rpm 2300 Bore and stroke 4.4" x 4.4" Compression ratio 16.5 to 1 Displacement 401 cu in Cranking system 12 volt electric Lubrication pressure Air cleaner dry type with replaceable paper element and automatic dust unloader Oil filter dual media full flow with replaceable element Oil cooler engine coolant heat exchanger for engine oil and radiator for transmission and hydraulic oil Fuel filter screen in tank dual replaceable paper elements with water traps Muffler was used Cooling medium temperature control thermostat.

CHASSIS Type standard Serial No G1015M C248889 Tread width rear 68" to 88" front 56" to 84" Wheel base 91.5" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 28.4" Vertical distance above roadway 38.0" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system selective gear fixed ratio with partial range operator controlled power shifting Advertised speeds mph first 1.55 second 1.99 third 2.19 fourth 2.81 fifth 3.29 sixth 4.23 seventh 4.40 eighth 5.09 ninth 5.65 tenth 6.55 eleventh 7.20 twelfth 9.26 thirteenth 10.82 fourteenth 13.92 fifteenth 14.48 sixteenth 18.62 reverse 1.93, 2.48, 6.34 and 8.16 Clutch single plate dry disc operated by foot pedal Brakes wet disc hydraulically actuated by two foot pedals which can be locked together Steering hydrostatic Turning radius (on concrete surface with brake applied) right 132" left 132" (on concrete without brake) right 156" left 156" Turning space diameter (on concrete surface with brake applied) right 287" left 287" (on concrete surface without brake) right 322" left 322" Power take-off 540 rpm at 1900 engine rpm and 1000 rpm at 1935 engine rpm.

REPAIRS and ADJUSTMENTS: No repairs or adjustments.

REMARKS: All test results were determined from observed data obtained in accordance with the SAE and ASAE test code. First, second and third gears were not run as it was necessary to limit the pull in fourth gear because of the stability formula. Sixteenth gear was not run as it exceeded 15 mph.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 1026.

L. F. LARSEN

Engineer-In-Charge

G. W. STEINBRUEGGE, Chairman

W. E. SPLINTER

D. E. LANE

Board of Tractor Test Engineers

EXPLANATION OF TEST REPORT

GENERAL CONDITIONS

Each tractor is a production model equipped for common usage. Power consuming accessories can be disconnected only when it is convenient for the operator to do so in practice. Additional weight can be added as ballast if the manufacturer regularly supplies it for sale. The static tire loads and the inflation pressures must conform to recommendations in the Tire Standards published by the Society of Automotive Engineers.

PREPARATION FOR PERFORMANCE RUNS

The engine crankcase is drained and refilled with a measured amount of new oil conforming to specifications in the operators manual. The fuel used and the maintenance operations must also conform to the published information delivered with the tractor. The tractor is then limbered-up for 12 hours on drawbar work in accordance with the manufacturer's published recommendations. The manufacturer's representative is present to make appropriate decisions regarding mechanical adjustments.

The tractor is equipped with approximately the amount of added ballast that is used during maximum drawbar tests. The tire tread-bar height must be at least 65% of new tread height prior to the maximum power run.

BELT OR POWER TAKE-OFF PERFORMANCE

Maximum Power and Fuel Consumption. The manufacturer's representative makes carburetor, fuel pump, ignition and governor control settings which remain unchanged throughout all subsequent runs. The governor and the manually operated governor control lever is set to provide the high-idle speed specified by the manufacturer for maximum power. Maximum power is measured by connecting the belt pulley or the power take-off to a dynamometer. The dynamometer load is then gradually increased until the engine is operating at the rated speed specified by the manufacturer for maximum power. The corresponding fuel consumption is measured.

Varying Power and Fuel Consumption. Six different horsepower levels are used to show corresponding fuel consumption rates and how the governor causes the engine to react to the following changes in dynamometer load: 85% of the dynamometer torque at maximum power; minimum dynamometer torque, $\frac{1}{2}$ of the 85% torque; maximum power, $\frac{1}{4}$ and $\frac{3}{4}$ of the 85% torque. Since a tractor is generally subjected to varying loads the average of the results in this test serve well for predicting the fuel consumption of a tractor in general usage.

DRAWBAR PERFORMANCE

All engine adjustments are the same as those used in the belt or power take-off tests. If the manufacturer specifies a different rated crankshaft speed for drawbar operations, then the position of the manually operated governor control is changed to provide the high-idle speed specified by the manufacturer in the operating instructions.

Varying Power and Fuel Consumption With Ballast. The varying power runs are made to show the effect of

speed-control devices (engine, governor, automatic transmission, etc.) on horsepower, speed and fuel consumption. These runs are made around the entire test course which has two 180 degree turns with a minimum radius of 50 feet. The drawbar pull is set at 3 different levels as follows: (1) as near to the pull at maximum power as possible and still have the tractor maintain the travel speed at maximum horsepower on the straight sections of the test course; (2) 75% of the pull at maximum power; and (3) 50% of the pull at maximum power. Prior to 1958, fuel consumption data (10 hour test) were shown only for the pull obtained at maximum power for tractors having torque converters and at 75% of the pull obtained at maximum power for gear-type tractors.

Maximum Power with Ballast. Maximum power is measured on straight level sections of the test course. Data are shown for not more than 12 different gears or travel speeds. Some gears or travel speeds may be omitted because of high slippage of the traction members or because the travel speed may exceed the safe-limit for the test course. The maximum safe speed for the Nebraska Test Course has been set at 15 miles per hour. The slippage limits have been set at 15% and 7% for pneumatic tires and steel tracks or lugs, respectively. Higher slippage gives widely varying results.

Maximum Pull without Ballast. All added ballast is removed from the tractor. The drawbar pull is determined at slip limits of 15% for pneumatic tires or 7% for steel tracks or lugs. The tractor is operated at the fastest possible travel speed.

Varying Power and Travel Speed with Ballast. Travel speeds corresponding to drawbar pulls beyond the maximum power range are obtained to show the "lugging ability" of the tractor. The run starts with the pull at maximum power; then additional drawbar pull is applied to cause decreasing speeds. The run is ended by one of three conditions: (1) maximum pull is obtained, (2) the maximum slippage limit is reached, or (3) some other operating limit is reached.

For additional information about the Nebraska Tractor Tests write to the Department of Agricultural Engineering, University of Nebraska, Lincoln, Nebraska.

